



Residential Grade

- 2 USB charging ports with a total output of 2.1 A
- Tamper Resistant (TR) Receptacles increase safety
- Charge electronic devices directly without an adapter
- Back and side wiring for easy installation
- Compliance with the NEC Section 406.11 code requirements
- Wall plate included (8831)
- Fits into a standard wall box

Plate Cover Information

- Made of polycarbonate
- High-impact resistance limits access to live parts due to breakage
- Smooth finish without recessed lines is easy to clean and maintain attractive appearance
- Various colors available

Tamper Resistant Receptacle with 2 USB Ports

DESCRIPTION	CAT. NO.	RATING	COLOR
Dual USB Charger with 15A Duplex Tamper Resistant Receptacle	13-USB-15R-TR-WH	Voltage: 125VAC, 60Hz Max load: 15A Output: 5VDC 2.1A	White
Dual USB Charger with 20A Duplex Tamper Resistant Receptacle	13-USB-20R-TR-WH	Voltage: 125VAC, 60Hz Max load: 20A Output: 5VDC 2.1A	White

TESTING & CODE COMPLIANCE:

- UL/CUL Listed
- ISO9001 Registered Manufacturing Facility

MATERIAL CHARACTERISTICS:

- Environmental:
Flammability UL94, V2 Rating
- Operating Temperature:
From -40°C (without impact)
to 75°C maximum continuous