



# **Recessed Lighting**

# 6" Sloped Ceiling Cans & Trim



11-R6SLNWIC





### TRIMS



Black Stepped Baffle 75W/R30 or PAR30



White Stepped Baffle 75W/R30 or PAR30



ed Baffle Specular Clear Reflector PAR30 75W/R30 or PAR30



Satin Nickel Eyeball 75W/R30 or PAR30



Eyeball-White 75W/R30 or PAR30



Polished Brass Eyeball 75W/R30 or PAR30

## **FEATURES**

For new work uses, this 6 IC Sloped incandescent recessed housing accommodates up to 75W R30/PAR 30 lamps with proper trim. Thermal protector safeguards against overheating, and housing is UL listed.

#### 11-R6SLNWIC

- Safe, Thermally Protected, for Damp Locations.
- Easy Access Housing.
- Adjustable Socket for flexibility in lamping options.
- Time Saving Junction Box Design.
- Easy Installation.
- Used for pitched ceilings 10-30 degrees
- UL damp location
- 7 x 7H

For Remodel uses, this 6 IC Sloped incandescent recessed housing accommodates up to 75W R30/PAR 30 lamps with proper trim. Thermal protector safeguards against overheating, and housing is UL listed.

#### 11-R6SLRMIC

- 6-1/2"W x 7-1/2"H
- For old work or remodel applications
- For direct contact with insulation
- Up to 75-watt lamp with proper trim
- UL Listed for both drywall and drop ceilings.
- Thermally-protected
- Adjustable lamp height
- UL listed for feed-through wiring and damp location

Also available in Gimbal rings.