




PROJECT	TYPE	CATALOG #



Series	Ø	H	Weight
11-CDR6-2L-LKFS-WHT	8.4"	4.2"	1.4 lbs
11-CDR6-2L-LKFS-SW	8.3"	4.4"	1 lbs

Example: 11-CDR6-2L-LKFS-WHT

MODEL	NOMINAL LUMEN OUTPUT (SELECTABLE)	KELVIN (SELECTABLE)	BAFFLE TYPE
11-CDR6	2L= 2,000lm / 1,500lm / 1,000lm 2L= 1,600lm / 1,200lm / 900lm	LKFS = 2.7K/3K/3.5K/4K/5K	WHT= White Baffle SW= Specular White

Specifications

Housing

- Aluminum housing.

Electrical

- Uses 20, 15, or 10 nominal watts.
- Universal 120-277 AC voltage (50-60Hz) is standard.
- Power factor > 0.90.
- 0-10VDC dimming is standard.

Optical System

- Field selectable 2700k (soft white), 3000k (warm white), 3500k (warm/neutral white), 4000k (neutral white), and 5000k (cool white) color temperatures.
- Long-life LEDs provide at least 70% of initial lumen output (L70) for 149,000 hours of operation.**
- Color rendering index (Ra) > 90.
- Field selectable lumen output: 11-CDR6-2L-LKFS-WHT = 2,000, 1,500, or 1,000 nominal lumens. 11-CDR6-2L-LKFS-SW = 1,600, 1,200, or 900 nominal lumens.

Mounting

- Easy installation in new construction or retrofit applications.
- Compatible with 6.30" ceiling cut-outs and 6" mounting frames.
- Type IC. Access above ceiling required. Covered ceiling mount only.

Code Compliance

- cETLus listed for wet locations not exceeding 45°C (113°F).
- Energy Star certified.
- Compatible for new construction and retrofit applications.
- Complies with FCC Part 15, class B.
- Complies with EN61000-4-5 surge protection (1kV).

Warranty

- 5-year warranty of all electronics and housing.

**L₇₀ hours are IES TM 21 11 calculated hours.