



Weight: 0.25 lbs.



MODEL	COLOR TEMPERATURE	
11-KOK-4EJCT09SR05	Selectable CCT	2700K 3000K 3500K 4000K 5000K

## FEATURES

- Field selectable 2700k (soft white), 3000k (warm white), 3500k (warm/neutral white), 4000k (neutral white), and 5000k (cool white) color temperatures.
- Long-life LEDs provide at least 70% of initial lumen output ( $L_{70}$ ) for 181,000 hours of operation.\*
- Color rendering index ( $R_a$ ) > 90.
- 600 nominal lumens.
- 7 nominal watts.
- 120 AC voltage (60Hz) is standard.
- Power factor > 0.90.
- Total harmonic distortion < 20%.
- Triac dimming.
- Aluminum housing.
- Easy installation in new construction or retrofit applications.
- Compatible with 4.30" ceiling cut-outs.
- Type IC. Access above ceiling required. Covered ceiling mount only.
- This device is not intended for use with emergency exits.

\* $L_{70}$  hours are IES TM-21-11 calculated hours.

## WARRANTY & LISTINGS

- cETLus listed for wet locations not exceeding 45°C (113°F).
- Energy Star certified.
- Compatible for new construction and retrofit applications.
- Complies with FCC Part 15, class B.
- Complies with EN61000-4-5 surge protection (0.5kV).
- 5-year warranty of all electronics and housing.