



COST LESS LIGHTING

05-SL-LKFS

LUMEN AND KELVIN FIELD SELECTABLE STRIP LIGHT

p. 866.633.6883 • f. 866.699.8099 • CostLessLighting.com

4ft. Weight: 4.5lbs./ **8ft.** Weight: 9lbs.



	4ft.	8ft.
L	47.3"	94.2"
W	3.3"	3.3"
H	3.5"	3.5"



**Wire Guard Optional
for increased protection**



MODEL	LENGTH	NOMINAL LUMEN OUTPUT		COLOR TEMPERATURE		OCCUPANCY SENSOR ¹²	INTERNALLY INSTALLED EMERGENCY DRIVERS ³
		SELECTABLE					
05-SL-LKFS	4FT 8FT	5L 10L	5200/4300/3600 10,000/8500/7100	LKFS	3K/4K/5K	OS = Passive infrared ODS = Microwave Blank = No occupancy sensor	EM5 = 650 lumens EM10 = 1,390 lumens EM13 = 1,780 lumens Blank = No emergencyh driver

FEATURES

- Field selectable 3500k (warm/neutral white), 4000k (neutral white), and 5000k (cool white) color temperatures.*
- Long-life LEDs provide 196,000 hours of operation with at least 70% of initial lumen output (L_{70}), and 60,000 hours with at least 90% of initial lumen output (L_{90}).^{**}
- LED chromaticity based on < 4-step ANSI quadrangles.
- LED color maintenance < 0.002 chromaticity shift ($\Delta u'v'$) over the initial 6,000 hours of operation.
- 05-SL-4FT-5L-LKFS provides a range of 3,700 to 5,200 nominal lumens and 138 to 152 lumens per watt (LPW).*
- 05-SL-8FT-10L-LKFS provides a range of 7,100 to 10,100 nominal lumens and 132 to 149 lumens per watt (LPW).*

- Universal 120-277 AC voltage (50-60Hz) is standard.
- 0-10vdc dimming drivers are standard.
- Power factor > 0.90.
- Total harmonic distortion < 20%.
- Color rendering index > 80.
- Steel housing and PMMA lens.
- Optional emergency drivers and occupancy sensors are available.
- Easy installation in new construction or retrofit.

^{**} L_{70} hours are IES TM-21-11 calculated hours

LIFE HOURS
196,000

WARRANTY/LISTING

- cULus approved for damp locations in ambient temperatures from -20°C to 50°C (-4°F to 122°F).
- Complies with FCC Part 15, Class A.
- Complies with IEEE C.62.41-1991, Class A input transient surge protection (1.0kV).
- 5-year warranty of all electronics and housing.

¹ Contact factory for other sensors.

² OS = passive infrared technology – features include on/off only. ODS = microwave technology – features include on/off, step-dimming, and daylight threshold. Default sensor settings: detection area = 100%, hold time = 5 seconds, stand-by period = 0 seconds, stand-by dimming level = 10%, daylight threshold = disabled. Remote control optional but not required, part number = HD03R.

³ See emergency driver compatibility list (page 2t).



COST LESS LIGHTING

05-SL-LKFS

LUMEN AND KELVIN

FIELD SELECTABLE STRIP LIGHT

p. 866.633.6883 • f. 866.699.8099 • CostLessLighting.com

COMPATIBLE EMERGENCY DRIVERS*

Emergency Driver Part Number	EM5		EM10		EM13	
Model	Watts	EM Lumens	Watts	EM Lumens	Watts	EM Lumens
05-SL-4FT-5L-LKFS	5.0	760	10.7	1627	13.7	2083
05-SL-8FT-10L-LKFS	5.0	760	10.7	1627	13.7	2083

* Suitable for ambient temperatures above 10°C (50°F).

ACCESSORIES

(Order Separately)

BLEM-CP-5C = Emergency driver - EM5
BLEM-CP-10C = Emergency driver - EM10
BLEM-CP-13C = Emergency driver - EM13

Wire Guard

SL-4FT-WG = Wire-guard kit – 4FT

* Suitable for ambient temperatures above 10°C (50°F).

COMPATIBLE EMERGENCY DRIVERS INTERNALLY INSTALLED ^{1 2}

Model	Emergency Options
05-SL-4FT-5L-LKFS 05-SL-8FT-10L-LKFS	EM5 EM10 EM13

¹ Suitable for ambient temperatures above 10°C (50°F).

² For list of remote mountable emergency drivers, see *ACCESSORIES*.

COMPATIBLE DIMMERS & CONTROLS

Manufacturer	Model Number	Dimming Range	Load Switching Capacity
Best Lighting	DWS-010V-T	10%-100%	600W
Best Lighting	DWS-010V-D	10%-100%	600W
Leviton	IP710-LFZ	10%-100%	1200W
Lutron	DVSTV	10%-100%	450W



COST LESS LIGHTING

05-SL-LKFS

LUMEN AND KELVIN FIELD SELECTABLE STRIP LIGHT

p. 866.633.6883 • f. 866.699.8099 • CostLessLighting.com

ELECTRICAL DATA

Series	Measurements	Low Lumens			Mid Lumens			High Lumens		
		3500K	4000K	5000K	3500K	4000K	5000K	3500K	4000K	5000K
05-SL-4FT-LKFS	Lumens	3690	3631	3722	4336	4317	4389	4876	5203	4908
	Watts	26	25	26	31	30	31	35	34	35
	Efficacy	143	143	144	140	143	142	138	152	139
	Input Current (A)	120V = 0.22A	120V = 0.21A	120V = 0.22A	120V = 0.26A	120V = 0.25A	120V = 0.26A	120V = 0.29A	120V = 0.28A	120V = 0.29A
		240V = 0.11A	240V = 0.10A	240V = 0.11A	240V = 0.13A	240V = 0.13A	240V = 0.13A	240V = 0.15A	240V = 0.14A	240V = 0.15A
		277V = 0.09A	277V = 0.09A	277V = 0.09A	277V = 0.11A	277V = 0.11A	277V = 0.11A	277V = 0.13A	277V = 0.12A	277V = 0.13A
05-SL-8FT-LKFS	Lumens	7251	7135	7314	8520	8483	8624	9553	10,124	9619
	Watts	55	55	55	60	60	60	70	68	70
	Efficacy	132	130	133	142	141	144	136	149	137
	Input Current (A)	120V = 0.46A	120V = 0.46A	120V = 0.46A	120V = 0.50A	120V = 0.50A	120V = 0.50A	120V = 0.58A	120V = 0.57A	120V = 0.58A
		240V = 0.23A	240V = 0.23A	240V = 0.23A	240V = 0.25A	240V = 0.25A	240V = 0.25A	240V = 0.29A	240V = 0.28A	240V = 0.29A
		277V = 0.20A	277V = 0.20A	277V = 0.20A	277V = 0.22A	277V = 0.22A	277V = 0.22A	277V = 0.25A	277V = 0.25A	277V = 0.25A

PHOTOMETRIC DATA

05-SL-4FT-5L-LKFS

Luminaire Data

Description	4' Strip Light 5L 5K - LKFS
Total Lumens	4,908
Input Wattage	35
Efficacy (lm/W)	139
Spacing Criterion (0-180°)	1.24
Spacing Criterion (90-270°)	1.36

Zonal Lumen Summary

Zone	Lumens	%Fixt
0-20°	470	9.6%
0-30°	1,002	20.4%
0-40°	1,653	33.7%
20-50°	1,877	38.2%
40-70°	1,927	39.3%
0-60°	3,009	61.3%
0-80°	4,024	82.0%
0-90°	4,338	88.4%
90-180°	570	11.6%
0-180°	4,908	100.0%

