



Lighting & Electrical Supply Catalog

costlesslighting.com
866-633-6883



**COST LESS
LIGHTING**



MULTI-PURPOSE AREA LIGHTS	3
BOLLARDS	3
WALL PACKS	4
CANOPY LIGHT	5
DUSK-TO-DAWN	5
HIGHBAYS	6
STRIPS LIGHTS	8
WRAPS	8
UNDERCABINET	9
VAPORTIGHT	10
GRID CEILING PANEL LIGHTS	11
LED REPLACEMENT TUBES	12
STAIRWELL LIGHT	12
ARCHITECTURAL RECESSED LIGHTS	13
LED RECESSED TRIMS & CANS	14
RETROFIT FLAT PANEL RECESSED LIGHTS	16
SURFACE MOUNTS	16
EXIT SIGN & EMERGENCY LIGHTING & COMBOS	18
EMERGENCY POWER SYSTEMS	20
SENSORS & DIMMERS	21
SWITCHES & RECEPTACLES	22
WIRE CONNECTORS / CABLE TIES / GOOF RINGS	23
CORDS / PLUGS / WHIPS	23

OUTDOOR

INDOOR

**LIFE
SAFETY**

ACCESSORIES



MULTI-PURPOSE AREA LIGHT PRO

- Field selectable output and color temperature
- Distribution Type III or Type V
- Universal voltage 120-277V or 277-480V
- 0-10v dimming
- Power factor >0.90
- CRI >80
- Optional NEMA photocell
- L70 = 162,000 hours



Mounting	
08-MPAL-ARM	Arm Mount
08-MPAL-ARM-A	Adjustable arm
08-MPAL-SF	Slip-fitter
08-MPAL-TM	Trunnion
08-MPALPRO-Yoke	Yoke



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
08-MPALPRO-24L-LKFS	26,600 lumens	178	150 lm/W	3000K/4000K/5000K	17"	12"	4"
	22,824 lumens	146	156 lm/W				
	16,173 lumens	100	162 lm/W				
08-MPALPRO-40L-LKFS	44,173 lumens	284	156 lm/w	3000K/4000K/5000K	23.5"	12"	4"
	37,248 lumens	232	160 lm/W				
	32,211 lumens	198	163 lm/W				

MULTI-PURPOSE AREA LIGHT

- Field selectable color temperature
- Universal voltage 120-277V
- 0-10v dimming
- Power factor >0.90
- CRI >80
- L70 = 149,000 hours.



Mounting	
08-MPAL-6Ft-Yoke	Yoke mount (6ft. & 3ft.)
08-MPAL-ST17	Line Voltage Ground Stake



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
08-MPAL-2L-KFS	2,180 lumens	15	145 lm/W	3500K/4000K/5000K	4.3"	1.7"	5.8"
08-MPAL-4L-KFS	4,695 lumens	30	155 lm/w	3500K/4000K/5000K	8.7"	1.9"	9"
08-MPAL-7L-KFS	7,170 lumens	49	147 lm/W	3500K/4000K/5000K	8.7"	1.9"	9"

BOLLARD LIGHTS

- Field selectable output and color temperature
- Universal voltage 120-277V
- 0-10v dimming
- Power factor >0.90
- CRI >80
- L70 = 163,000 hours.
- Black and Bronze housing colors available.



Mounting	
06-BOL-R-MISBT	Anchor Bolt for Round bollard
06-BOL-S-MISBT	Anchor Bolt for Square bollard



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
06-BOL-R-3L-LKFS	3,244 lumens	22	145 lm/W	3000K/4000K/5000K	6"	6"	42"
	2,686 lumens	19	145 lm/W				
	1,974 lumens	14	144 lm/W				
06-BOL-S-3L-LKFS	3,047 lumens	23	135 lm/w	3000K/4000K/5000K	6"	6"	42"
	2,450 lumens	18	135 lm/W				
	1,790 lumens	14	130 lm/W				
06-BOL-RD-3L-LKFS	3,249 lumens	22	145 lm/W	3000K/4000K/5000K	6"	6"	44"
	2,530 lumens	17	145 lm/W				
	1,818 lumens	12	150 lm/W				
06-BOL-RDL-2L-LKFS	1,692 lumens	22	75 lm/W	3000K/4000K/5000K	6"	6"	44"
	1,351 lumens	17	80 lm/W				
	973 lumens	12	80 lm/W				

*Nominal values shown for CCT set at 4000K



TRADITIONAL WALL PACK

- Field selectable output and color temperature
- Universal voltage 120-277V
- Power factor >0.90
- CRI >70
- Glass lens.
- L70 = 130,000 hours



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
06-WPT-7L-LKFS	7,290 lumens	49	149 lm/W	3000K/4000K/5000K	14"	9"	5"
	5,853 lumens	38	150 lm/W				
	4,668 lumens	29	151 lm/W				
06-WPT-10L-LKFS	10,652 lumens	74	144 lm/W	3000K/4000K/5000K	14"	9"	5"
	8,785 lumens	57	154 lm/W				
	6,741 lumens	42	159 lm/W				
06-WPT-15L-LKFS	15,552 lumens	110	141 lm/W	3000K/4000K/5000K	14"	9"	5"
	13,506 lumens	91	149 lm/W				
	10,548 lumens	69	153 lm/W				

ADJUSTABLE WALL PACK

- Field selectable output and color temperature
- Universal voltage 120-277V
- Power factor >0.90
- CRI >80
- Polycarbonate lens
- L70 = 146,000 hours



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
06-WPA-5L-LKFS	5,084 lumens	34	151 lm/W	3000K/4000K/5000K	6.5"	4"	8"
	3,842 lumens	25	151 lm/W				
	3,002 lumens	20	154 lm/W				
06-WPA-10L-LKFS	10,734 lumens	71	150 lm/w	3000K/4000K/5000K	8.5"	5"	11"
	9,032 lumens	59	153 lm/W				
	7,028 lumens	45	157 lm/W				

ECONOMY/SMALL WALL PACK

- Field selectable output and color temperature
- Universal voltage 120-277V
- Power factor >0.90
- CRI >80
- Polycarbonate lens
- L70 = 156,000 hours



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
06-WPE-3L-LKFS	3,327 lumens	24	140 lm/W	3000K/4000K/5000K	9"	6"	2.5"
	2,709 lumens	19	143 lm/W				
	2,090 lumens	14	145 lm/W				

* Nominal values shown for CCT set at 4000K



FULL CUT-OFF WALL PACK

- Field selectable output and color temperature
- Universal voltage 120-277V
- Power factor >0.90
- CRI >80
- Polycarbonate lens
- L70 = 136,000 hours



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
06-WPFC-8L-LKFS	8,682 lumens	57	152 lm/W	3000K/4000K/5000K	14"	9"	6"
	7,048 lumens	46	156 lm/W				
	5,526 lumens	35	161 lm/W				
06-WPFC-15L-LKFS	16,848 lumens	113	149 lm/w	3000K/4000K/5000K	14"	9"	6"
	13,760 lumens	92	154 lm/W				
	10,987 lumens	71	159 lm/W				

CANOPY LIGHT

- Field selectable output and color temperature
- Universal voltage 120-277V
- 0-10Vdc dimming
- Power factor >0.90
- CRI >80
- Optional factory installed microwave and dimming sensors
- L70 = 149,000 hours
- Available in White or Bronze finish



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
06-CP-10L-LKFS	10,500 lumens	69	150 lm/W	3000K/4000K/5000K	10.5"	9.6"	3.4" (with sensor)
	8,250 lumens	51	160 lm/W				
	6,950 lumens	43	165 lm/W				

DUSK-TO-DAWN LIGHT

- Universal voltage 120-277V
- Power factor >0.90
- CRI >80
- L70 = 163,000 hours
- NEMA photocell standard
- Polycarbonate lens



Mounting
08-LR3-DDALS5L-ARM Mounting arm with bracket



Product Number	Lumen Output	Watts	Efficacy	CCT	Length (in)	Width (in)	Height (in)
08-DDAL-5L-5k-PC	4,900 lumens	37	133 lm/W	5000K	10"	7"	6"



PREMIUM LINEAR HIGH BAY

- Universal voltage 120-277V; optional 347-480V
- Power factor >0.90
- Sensor ready
- 0-10Vdc dimming
- Field selectable output and color temperature
- Optional occupancy sensor
- L70 = 134,000 hours
- Emergency drivers available
- Optional narrow or wide distribution



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
07-HBLSR-181512L-LKFS	18,085 lumens 14,555 lumens 12,007 lumens	120 96 76	150 lm/W 152 lm/W 158 lm/W	4000K/5000K	16.5"	10.25"	1.8"
07-HBLSR-241815L-LKFS	24,047 lumens 18,017 lumens 15,021 lumens	158 115 94	152 lm/W 157 lm/W 159 lm/W	4000K/5000K	23"	10.25"	1.8"
07-HBLSR-363024L-LKFS	35,517 lumens 30,037 lumens 24,049 lumens	237 193 152	150 lm/W 156 lm/W 158 lm/W	4000K/5000K	31"	10.25"	1.8"
07-HBLSR-604836L-LKFS	60,104 lumens 48,182 lumens 37,049 lumens	404 312 236	149 lm/W 154 lm/W 157 lm/W	4000K/5000K	44"	10.25"	1.8"

LINEAR ADJUSTABLE HIGH BAY

- Universal voltage 120-277V
- Power factor >0.90
- CRI >80
- 0-10Vdc dimming
- Optional Passive Infrared or microwave sensor
- L70 = 174,000 hours
- Optic panels rotate up to 135 degrees



Accessories Sold Separately

07-HBLA-WGK-24X4	Wire-guard kit – 15L & 23L
07-HBLA-WGK-24X5	Wire-guard kit – 30L
07-LEDHB-PMK-S	Pendant mount kit – all models
07-LEDHB-SMK-S	Surface mount kit – all models

Product Number	Lumen Output	Watts	Efficacy	CCT	Length (in)	Width (in)	Height (in)
07-HBLA-15L-4K	15,297 lumens	109	140 lm/W	4000K	26"	12"	2"
07-HBLA-15L-5K	15,471 lumens	109	141 lm/W	5000K	26"	12"	2"
07-HBLA-23L-4K	22,970 lumens	166	139 lm/W	4000K	26"	12"	2"
07-HBLA-23L-5K	23,223 lumens	166	140 lm/W	5000K	26"	12"	2"
07-HBLA-30L-4K	30,394 lumens	217	140 lm/W	4000K	26"	12"	2"
07-HBLA-30L-5K	30,741 lumens	217	142 lm/W	5000K	26"	12"	2"

* Nominal values shown for CCT set at 4000K



PREMIUM ROUND HIGH BAY

- Universal voltage 120-277V; optional 347-480V
- Power factor >0.90
- 0-10Vdc dimming
- Field selectable output and color temperature
- Sensor Ready- screw in receptacle
- Optional Passive Infrared photocell (PIR) or Microwave sensor sold separately
- L70 = 146,000 hours
- Available in black or white



Accessories Sold Separately
 07-HD07VR-PH-1 = Passive Infrared Sensor
 07-HD07VR-MH-B-1 = Microwave step-dimming sensor
 07-HBSD-325W-480-277 = 347-480V step-down transformer
 07-HBRSR-ALREF-S = 90° aluminum reflector - 07-HBRSR-221816L-4K5K models
 07-HBRSR-PCREF-S = 90° polycarbonate reflector - 07-HBRSR-221816L-4K5K models
 07-HBRSR-ALREF-L = 90° aluminum reflector - 07-HBRSR-353024L-4K5K models
 07-HBRSR-PCREF-L = 90° polycarbonate reflector - 07-HBRSR-353024L-4K5K-4K5K models
 07-HBRSR-YOKE-WHT = Yoke mount - all models - white
 07-HBRSR-YOKE-BLK = Yoke mount - all models - black
 07-LEDHBRN-PSH-PRM-V2 = Pendant snap hook - all models

Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Diameter (in)	Height (in)
07-HBRSR-221816L-LKFS	22,935 lumens	147	156 lm/W	4000K/5000K	10.6"	5.5"
	18,790 lumens	115	163 lm/W			
	15,891 lumens	95	168 lm/W			
07-HBRSR-353024L-LKFS	35,716 lumens	229	156 lm/W	4000K/5000K	13"	5.6"
	30,801 lumens	192	160 lm/W			
	24,368 lumens	146	167 lm/W			

HIGH-LUMEN LINEAR HIGH BAY

- Universal voltage 120-277V; optional 347-480V
- Power factor >0.90
- CRI >80
- 0-10Vdc dimming
- PMMA frosted lens
- L70 = 130,000 hours
- Emergency drivers available
- Surface and cable mounting methods available



Accessories

07-HBLE-SMK-4.4WIDE	Surface-mounting kit
07-LEDFHB-CMK3	Cable-mounting kit, 3 meters long
07-LEDFHB-CMK5	Cable-mounting kit, 5 meters long
07-HBLE-WG-47X23	Wire-guard

Product Number	Lumen Output	Watts	Efficacy	CCT	Length (in)	Width (in)	Height (in)
07-HBLE-78L-4K	77,545 lumens	523	148 lm/W	4000K	46.5"	22.9"	2.2"
07-HBLE-78L-5K	77,601 lumens	511	152 lm/W	5000K	46.5"	22.9"	2.2"

* Nominal values shown for CCT set at 4000K



STRIP LIGHT

- Universal voltage 120-277V
- Power factor >0.90
- CRI >80
- 0-10Vdc dimming
- Field selectable output and color temperature
- Optional passive infrared (PIR) or microwave sensor
- L70 = 196,000 hours
- Emergency drivers available



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
05-SL-4FT-5L-LKFS	5,203 lumens	34	152 lm/W	3500K/4000K/5000K	47.3"	3.3"	3.5"
	4,317 lumens	30	143 lm/W				
	3,631 lumens	25	143 lm/W				
05-SL-8FT-10L-LKFS	10,124 lumens	68	149 lm/W	3500K/4000K/5000K	94.2"	3.3"	3.5"
	8,483 lumens	60	141 lm/W				
	7,135 lumens	55	130 lm/W				

STRIP LIGHT SLIM

- Universal voltage 120-277V
- Power factor >0.90
- CRI >80
- 0-10Vdc dimming
- Field selectable output and color temperature
- Optional passive infrared (PIR) or microwave sensors
- L70 = 196,000 hours
- Emergency drivers available



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
05-SLS-4FT-5L-LKFS	5,025 lumens	33	151 lm/W	3500K/4000K/5000K	47.3"	2.4"	2.8"
	4,305 lumens	30	143 lm/W				
	3,622 lumens	25	143 lm/W				
05-SLS-8FT-10L-LKFS	9,976 lumens	67	149 lm/W	3500K/4000K/5000K	94.2"	2.4"	2.8"
	8,862 lumens	58	152 lm/W				
	7,567 lumens	48	156 lm/W				

PREMIUM WRAP LIGHT

- Universal voltage 120-277V
- Power factor >0.90
- CRI >80
- 0-10Vdc dimming
- Field selectable output and color temperature
- Optional passive infrared (PIR) or microwave sensor
- L70 = 196,000 hours
- Emergency drivers available



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
05-WR-5L-LKFS	5,837 lumens	39	149 lm/W	3500K/4000K/5000K	47.7"	7.1"	2.8"
	4,932 lumens	32	152 lm/W				
	4,336 lumens	28	154 lm/W				

* Nominal values shown for CCT set at 4000K



ECONOMY WRAP LIGHT

- Universal voltage 120-277V
- Power factor >0.90
- CRI >80
- 0-10Vdc dimming
- Field selectable output and color temperature
- L70 = 196,000 hours



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
05-WRE-6L-LKFS	5,880 lumens	45	131 lm/W	3500K/4000K/5000K	47.6"	5.4"	2"
	5,017 lumens	40	129 lm/W				
	3,925 lumens	30	131 lm/W				

ECONOMY UNDER CABINET LIGHT

- Standard 120Vac input
- Power factor >0.90
- CRI >90
- Triac dimming
- Field selectable color temperature
- L70 = 196,000 hours



Product Number	Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
14-UCE-9-KFS	412	5	86 lm/W	27K/30K/35K/40K/50K	9"	3.5"	1"
14-UCE-12-KFS	450	5	92 lm/W	27K/30K/35K/40K/50K	12"	3.5"	1"
14-UCE-18-KFS	770	9	88 lm/W	27K/30K/35K/40K/50K	18"	3.5"	1"
14-UCE-21-KFS	764	9	90 lm/W	27K/30K/35K/40K/50K	21"	3.5"	1"
14-UCE-24-KFS	803	9	91 lm/W	27K/30K/35K/40K/50K	24"	3.5"	1"
14-UCE-33-KFS	1,245	14	91 lm/W	27K/30K/35K/40K/50K	33"	3.5"	1"
14-UCE-42-KFS	1,543	18	88 lm/W	27K/30K/35K/40K/50K	42"	3.5"	1"

* Nominal values shown for CCT set at 4000K



VAPOR-TIGHT LIGHT

- Universal voltage 120-277V
- Power factor >0.90
- CRI >80
- L70 = 137,000 hours
- Field Selectable Color Temperature
- ETL Sanitation listed for non-splash food zones to comply with NSF/ANSI 2 standards
- NEMA 4x



Product Number	Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
05-VT-6L-KFS	6,256 lumens	42	148 lm/W	3500K/4000K/5000K	45.7"	4.7"	4.3"
05-VT-14L-KFS	14,327 lumens	93	156 lm/W	3500K/4000K/5000K	50"	10"	4.1"
05-VT-20L-KFS	21,447 lumens	140	152 lm/W	3500K/4000K/5000K	50"	10"	4.1"

VAPOR-TIGHT SLIM LIGHT

- Universal voltage 120-277V
- Power factor >0.90
- CRI >80
- L70 = 187,000 hours
- Emergency Drivers available
- Field Selectable output and color temperature
- Optional occupancy sensor



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
05-VTS-7L-LKFS	7,611 lumens	51	149 lm/W	3500K/4000K/5000K	47"	3.8"	3"
	6,198 lumens	43	144 lm/W				
	5,303 lumens	36	146 lm/W				

* Nominal values shown for CCT set at 4000K



CENTER BASKET

- Universal voltage 120-277V
- Power factor >0.90
- Field selectable output and color temperature
- CRI >80
- 0-10Vdc dimming
- PMMA lens
- L70 = 196,000 hours
- Emergency drivers available



Mounting Accessories and Emergency Drivers (Sold Separately)

05-SMKT-22	Surface Mount Kit for 2x2 panel
05-SMKT-24	Surface Mount Kit for 2x4 panel
05-FLANGEKIT22-ET	Flange Mounting Kit for 2x2 panel
05-FLANGEKIT24-ET	Flange Mount Kit for 2x4 Panel
05-PNL-CM	Cable Mounting Kit
03-BLEM-CP-5C	Remote Mount Emergency driver - EM5
03-BLEM-CP-10C	Remote Mount Emergency driver - EM10
03-BLEM-CP-13C	Remote Mount Emergency driver - EM13



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
05-CB22-4L-LKFS	4,370 lumens	31	140 lm/W	3500K/4000K/5000K	23.7"	23.7"	2"
	3,772 lumens	27	142 lm/W				
	3,176 lumens	22	144 lm/W				
05-CB-24-6L-LKFS	5,858 lumens	43	137 lm/W	3500K/4000K/5000K	47.8"	23.7"	2"
	5,062 lumens	36	139 lm/W				
	4,556 lumens	32	141 lm/W				

PANEL LIGHTS

- Universal voltage 120-277V
- Power factor >0.90
- Field selectable output and color temperature
- CRI >80
- 0-10Vdc dimming
- PMMA lens
- L70 = 144,000 hours
- Emergency drivers available
- Flicker-Free per IEEE1789-2015



Mounting Accessories (Sold Separately)

05-SMKT-14	Surface Mount Kit for 1x4 panel
05-SMKT-22	Surface Mount Kit for 2x2 panel
05-SMKT-24	Surface Mount Kit for 2x4 panel
05-FLANGEKIT14-ET	Flange mount kit for 1x4 panel
05-FLANGEKIT22-ET	Flange Mount Kit for 2x2 panel
05-FLANGEKIT24-ET	Flange Mount Kit for 2x4 Panel
05-PNL-CM	Cable Mounting Kit



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
05-PNL1X4-40L-LKFS	4,300 lumens	33	131 lm/W	3500K/4000K/5000K	47.7"	11.8"	1.5"
	3,700 lumens	27	137 lm/W				
	2,730 lumens	19	140 lm/W				
05-PNL2X2-40L-LKFS	4,290 lumens	32	135 lm/W	3500K/4000K/5000K	23.7"	23.7"	1.5"
	3,810 lumens	27	142 lm/W				
	2,800 lumens	19	145 lm/W				
05-PNL2X4-50L-LKFS	5,250 lumens	37	141 lm/W	3500K/4000K/5000K	47.7"	23.7"	1.5"
	4,575 lumens	32	144 lm/W				
	3,323 lumens	23	148 lm/W				

* Nominal values shown for CCT set at 4000K



T8 LED REPLACEMENT LAMPS

- Universal voltage 120-277V
- Non-dimming
- CRI>80
- L70 = 54,000 hours
- 02-T8LIDFH11-2200-4FT-CBA-7T
- 02-T8L-7X (8-ft) Series- Double-ended, integrated driver, Type B for bypass only
- 4-ft lamp Series- Single or double-ended, integrated driver, Type B for bypass only



Product Number	Lumen Output	Watts	Efficacy	CCT	Length (in)	Width (in)	Height (in)
02-T8LIDFH11-2200-4FT-CBA-7T	2,200 lumens	17	130 lm/W	4000K	47.2"	1"	1"
02-T8LIDFH11-2200-4FT-EBA-7T	2,200 lumens	17	130 lm/W	5000K	47.2"	1"	1"
02-T8LIDFH11-5000-8FT-EBA-7X	5,500 lumens	40	138 lm/W	5000K	93.2"	1"	1"
02-L8L1-BPMFH-G2-17W-A8TSE2200-4C	2,100 lumens*	17*	124 lm/W*	Selectable 27 / 30 / 35 / 40 / 50 / 6000K	47.2"	1"	1"

T5 LED Replacement Lamps

- Universal 120-277Vac input
- Non-dimming
- L70 = 54,000 hours
- CRI>80
- Double-ended, integrated driver, Type B for bypass only



Product Number	Lumen Output	Watts	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
02-T5L-ISFH14-3500-4FT-EBA-01	3,500 Lumens	25	140 Lm/W	5000	45.2"	0.7"	0.7"

STAIRWELL LIGHT

- Universal voltage 120-277V
- Power factor >0.90
- CRI >80
- 0-10Vdc dimming
- Optional occupancy/dimming sensor
- L70 = 190,000 hours
- Emergency drivers available
- Field selectable output and color temperature



Product Number	Selectable Lumen Output*	Watts*	Efficacy	Selectable CCT*	Length (in)	Width (in)	Height (in)
05-SW-LKFS	6,499 lumens 4,941 lumens 4,311 lumens	45 33 28	146 lm/W 150 lm/W 152 lm/W	3500K/4000K/5000K	48"	4.5"	4"

* Nominal values shown for CCT set at 4000K



DEEP ARCHITECTURAL LED RECESSED DOWNLIGHTS & FRAME KITS

- Universal 120-277V
- 0-10V Dimming
- CRI>80
- New Construction or Remodel application
- Architectural frames with C channel and flat hanger bars (ordered seperately) for tie-down to ceiling grids. ZZ-BARHANGER-ARCHCAN-FLAT27"



Trim Part	Frame Kit Part	Lumen Output	Watts	Efficacy	Available CCT	Aperature
11-4ARCH-LED-21TR-3K	11-4ARCH-LED-21	1590 lumens	21	76 lm/W	3000 Kelvin	4"
11-4ARCH-LED-28TR	11-4ARCH-LED-28	1940 Lumens	28	70 lm/W	4000 Kelvin	4"
11-6ARCH-LED-TR28	11-6ARCH-LED-28	2210 Lumens	28	79 lm/W	3000 Kelvin	6"
11-6ARCH-LED-TR48	11-6ARCH-LED-48	3770 Lumens	48	79 lm/W	4000 Kelvin	6"
11-8ARCH-LED-TR40	11-8ARCH-LED-40	3090 Lumens	40	77 lm/W	4000 Kelvin	8"
11-8ARCH-LED-TR52	11-8ARCH-LED-52	4530 Lumens	52	87 lm/w	4000 Kelvin	8"

ARCHITECTURAL LED DOWNLIGHT

- Universal Voltage 120-277V
- Field selectable output and color temperature
- 0-10Vdc dimming
- Power factor >0.90
- L70 = 149,000 hours
- IC rated
- New construction or retrofit applications



Product Number	Selectable Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
11-CDR4-1L-LKFS-WHT (White Baffle)	1,000 lumens 800 lumens 500 lumens	12 9 6	83 lm/W 89 lm/W 83 lm/W	2700K/3000K/4000K/5000K	5.1"	5.1"	3.2"
11-CDR4-1L-LKFS-SW (Specular White)	1,000 lumens 800 lumens 500 lumens	12 9 6	83 lm/W 89 lm/W 83 lm/W	2700K/3000K/4000K/5000K	5.1"	5.1"	3.2"
11-CDR6-2L-LKFS-WHT	2,000 lumens 1,500 lumens 1,000 lumens	20 15 10	100 lm/W	2700K/3000K/4000K/5000K	8.4"	8.4"	4.2"
11-CDR6-2L-LKFS-SW	1,600 lumens 1,200 lumens 900 lumens	20 15 10	100 lm/W	2700K/3000K/4000K/5000K	8.4"	8.4"	4.2"
11-CDR8-5L-LKFS-WHT	5,000 lumens 4,000 lumens 3,000 lumens	50 40 30	100 lm/W	2700K/3000K/4000K/5000K	10"	10"	4.5"

* Nominal values shown for CCT set at 4000K



2" CANS AND TRIMS

- Dedicated 120vac input
- IC Rated
- Triac dimming with most line voltage dimmers
- CRI>90
- L70 = 50,000 hours



Trim Part	Description	Lumen Output*	Watts*	Efficacy*	Available CCT	Length (in)	Width (in)	Height (in)
11-LED-2T-BW-SQ	Square White Baffle Trim	600 lumens	9	67 lm/W	3000K/4000K	3.125"	3.125"	2.625"
11-LED-2T-GRW-SQ	Square White Adjustable Gimbal Trim	600 lumens	9	67 lm/W	3000K/4000K	3.125"	3.125"	1.75"
11-LED-2T-BW	Round White Baffle Trim	600 lumens	9	67 lm/W	3000K/4000K	3.125"	3.125"	2.75"

2" Dedicated LED IC Rated Recessed Cans

New Construction Can	Remodel Can
11-R2LEDICN-AT-QN	11-R2LEDICR-IC-Q



3" CANS AND TRIMS

- Dedicated 120vac input
- IC Rated
- Triac dimming with most line voltage dimmers
- CRI>90
- L70 = 50,000 hours
- E26 Edison Adapter for retrofit applications included



Trim Part	Description	Lumen Output*	Watts*	Efficacy*	Available CCT	Length (in)	Width (in)	Height (in)
11-3BRKT-BW	Round White Baffle Trim	560 lumens	9	62 lm/W	3000K/4000K	4.375"	4.375"	2.75"

3" Dedicated LED IC Rated Recessed Cans

New Construction Can	Remodel Can
11-R350ICATLEDNND-QN	11-R350ICATLEDNRND-QN





4" CANS AND TRIMS

- Standard 120Vac input
- IC Rated
- Triac dimming
- CRI>90
- L70 = 119,000 hours
- E26 Edison Adapter for retrofit applications included
- Selectable color temperature



Trim Part	Description	Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
11-MODR4-7L-KFS	Round White Baffle Trim	700 lumens	10	70 lm/W	27/30/35/40/50 Kelvin	5.1"	5.1"	2.3"

4" Dedicated LED IC Rated Recessed Cans	
New Construction Can	Remodel Can
11-4C-LED-NIC-NND	11-4C-LED-RIC-NND



6" CANS AND TRIMS

- Standard 120Vac input
- IC Rated
- Triac dimming
- CRI>90
- L70 = 119,000 hours
- E26 Edison Adapter for retrofit applications included
- Selectable color temperature



Trim Part	Description	Lumen Output*	Watts*	Efficacy*	Selectable CCT	Length (in)	Width (in)	Height (in)
11-MODR6-10L-KFS	Round White Baffle Trim	1000 lumens	14	71 lm/W	27/30/35/40/50 Kelvin	7.4"	7.4"	2.4"

6" Dedicated LED IC Rated Recessed Cans	
New Construction Can	Remodel Can
11-6C-LED-NIC-NND	11-6C-LED-RIC-NND



* Nominal values shown for CCT set at 4000K



6" SLOPED INCANDESCENT RECESSED CANS & TRIMS

- Adjustable socket
- For pitched ceilings 10-30 degrees
- Accommodates up to 75W R30/PAR30 Incandescent lamps
- Thermal protection
- IC Rated



Trim Part	Description	Lamping	Trim Color	Baffle Color
11-6SLWSTEP	Sloped White Baffle Trim	E26 PAR30/R30 up to 75W	White	White
11-6SLBSTEP	Sloped Black Baffle Trim	E26 PAR30/R30 up to 75W	White	Black

6" Sloped Ceiling IC Rated Recessed Cans	
New Construction Can	Remodel Can
11-R6SLNWIC	11-R6SLRMIC



FLAT PANEL LIGHT

- Dedicated 120V (60Hz)
- Power factor >0.90
- Triac dimming
- Field selectable color temperature
- L70 = 181,000 hours (4-inch); L70 = 173,000 hours (6-inch)



Product Number	Lumen Output*	Watts*	Efficacy*	Selectable 5CCT	Length (in)	Width (in)	Height (in)
11-FPR4-6L-KFS	600 lumens	7	85 lm/W	2700K/3000K/3500/4000K/5000K	4.7"	4.7"	0.8"
11-FPR6-10L-KFS	1,000 lumens	15	66 lm/W	2700K/3000K/3500/4000K/5000K	6.7"	6.7"	0.8"

SURFACE MOUNT DOWNLIGHT

- Dedicated 120V (60Hz)
- Power factor >0.90
- Triac dimming
- Field selectable color temperature
- L70 = 119,000 hours
- Trim colors available: White, Nickel, Black
- Glass lens



Product Number	Housing Color	Lumen Output*	Watts*	Efficacy*	Selectable 5CCT	Length (in)	Width (in)	Height (in)
11-DL9-11L-KFS	White Brushed Nickel Bronze	1,100 lumens	18	61 lm/W	2700K/3000K/3500K/4000K/5000K	9"	9"	2"

* Nominal values shown for CCT set at 4000K



SURFACE MOUNT LIGHT

- Dedicated 120V (60Hz)
- Power factor >0.90
- Field selectable color temperature
- CRI >80
- Triac Dimming
- Polycarbonate lens
- L70 = 157,000 hours



Product Number	Lumen Output*	Watts*	Efficacy*	Selectable 5CCT	Length (in)	Width (in)	Height (in)
05-SMR11-KFS	1,000 lumens	14	71 lm/W	2700K/3000K/3500K/4000K/5000K	11"	11"	3"
05-SMR14-KFS	1,400 lumens	20	70 lm/W	2700K/3000K/3500K/4000K/5000K	14"	14"	3"
05-SMS12-KFS	1,000 lumens	14	71 lm/W	2700K/3000K/3500K/4000K/5000K	12"	12"	3"
05-SMS14-KFS	1,500 lumens	20	75 lm/W	2700K/3000K/3500K/4000K/5000K	14"	14"	3"

DOUBLE-RING, SURFACE-MOUNT LIGHT

- Dedicated 120V (60Hz)
- Power factor >0.90
- Field selectable color temperature
- CRI >90
- Triac dimming
- Polystyrene lens
- L70 = 93,000 hours
- Brushed nickel ring color



Product Number	Lumen Output*	Watts*	Efficacy*	Selectable 5CCT	Length (in)	Width (in)	Height (in)
05-DR10-KFS	1,000 lumens	15	67 lm/W	2700K/3000K/3500K/4000K/5000K	10"	10"	3"
05-DR14-KFS	1,800 lumens	20	90 lm/W	2700K/3000K/3500K/4000K/5000K	14"	14"	4"
05-DR18-KFS	2,000 lumens	20	100 lm/W	2700K/3000K/3500K/4000K/5000K	18"	18"	4.5"

DISK LIGHT

- Dedicated 120V (60Hz)
- Power factor >0.90
- Triac dimming
- Field selectable color temperature
- L70 = 119,000 hours



Product Number	Lumen Output*	Watts*	Efficacy*	Selectable 5CCT	Length (in)	Width (in)	Height (in)
11-DK6-10L-KFS	1,000 lumens	15	66 lm/W	2700K/3000K/3500K/4000K/5000K	7.2"	7.2"	1.4"



Die-Cast Aluminum Exit Sign

- Dual 120/277 voltage
- Premium, die-cast aluminum housing
- Internal automatic switching to emergency battery mode
- Meets UL924, NFPA 101 Life Safety code



Product Number	No. of Faces	Letter Color	Housing Color	Battery	Options
04-XDC	Single Double Universal Single/ Double	Red Green	White Black Brushed Aluminum	AC-Only EM-Battery Back-up	Self-Diagnostic Dual Circuit Tamper-proof Assembled in USA

Edge-Lit Exit Sign

- Dual 120/277 voltage
- Premium, extruded aluminum housing
- Internal automatic switching to emergency battery mode
- Mounting canopy for top, end or back mounting
- Meets UL924, NFPA 101 Life Safety code



Product Number	No. of Faces	Letter Color	Panel Color	Housing Color	Battery	Options
04-XEDU	Single Double	Red Green	Clear Mirror White	White Black Aluminum	AC-Only EM-Battery Back-up	Self-Diagnostic Dual Circuit (120V or 277V0) Special Wording Assembled in USA

Slim Profile LED Thermoplastic Exit Sign

- Dual 120/277 voltage
- Red/Green Selectable available
- Engineering grade, 5VA flame retardant Thermoplastic
- Internal automatic switching to emergency battery mode
- Mounting Canopy for top or side mounting or Universal KO for wall mount
- Meets UL924, NFPA 101 Life Safety code



Product Number	LED/Letter Color	Housing Color	Battery	Options	
04-X	Red Green Red/Green Selectable	White Black	AC-Only EM-Battery Back-up	Self-Diagnostic Dual Circuit Custom Wording Assembled in USA	SL- Low Profile



Exit/Emergency Two-Head Thermoplastic Combo Unit

- Dual 120/277 voltage
- Red/Green Selectable available
- 1.5-watt (3 LEDs x 0.50 watt) per head;
- 3.6V Long-life rechargeable NiCad battery;
- Internal automatic switching to emergency battery mode
- Engineering grade, 5VA flame retardant Thermoplastic
- Mounting Canopy for top or side mounting or Universal KO for wall mount
- Meets UL924, NFPA 101 Life Safety code



Product Number	No. of Faces	LED/Letter Color	Housing Color	Options
04-CEM	Universal Single/Double	Red Green RED/GREEN Selectable	White Black	Remote Capacity Self-Diagnostic Assembled in USA

Reduced Profile LED Adjustable Two-Head Emergency Unit

- Dual 120/277 voltage
- 1.5-watt (3 LEDs x 0.50 watt) per head;
- 3.6V Long-life rechargeable NiCad battery;
- Internal automatic switching to emergency battery mode
- Engineering grade, 5VA flame retardant Thermoplastic
- Meets UL924, NFPA 101 Life Safety code



Product Number	Housing Color	Options
04-EM	White Black	Self-Diagnostic Remote Capacity

Decorative Outdoor LED AC/Emergency Unit

- 4.8V long life, rechargeable NiCad Battery
- Automatic Emergency on switch
- 90 minutes illumination
- Self-Diagnostic monthly, bi-annual and annual testing
- Photocell standard
- Optional internal heater for extreme cold weather
- CEC Title 20 certified optional
- Meets UL924, NFPA 101 Life Safety code



Product Number	Housing Color	Voltage	Wattage	Output (Lumens)
04-WPED-ACEM-EM	White Black Dak Bronze Nickel	Universal 120-277V	12W	1,286 (AC mode) 350 (DC mode)

LIFE SAFETY



Micro/Mini/Large Inverter Emergency Power Systems

Electrical inverter systems for powering up to 1150W of incandescent, fluorescent, induction or LED lighting loads. Pulse width modulated (PWM) output design provides clean, 60 Hz. sinusoidal emergency power to loads.



Product Number	Capacity	Mounting	Options
03-MPS	20 Watts 32 Watts 35 Watts 55 Watts	Surface Recessed Ceiling T-Grid	Self-Diagnostics CEC-Title 20 Compliant Remote Test Switch Panel
03-PINV	55 Watts/125VA 110 Watts/125VA 110Watts/250VA 220Watts/250VA	Surface Recessed Ceiling T-Grid	Self-Diagnostics CEC-Title 20 Compliant Remote Test Switch Panel 4C- 4-output Circuit Switching AO-Adjustable Output/Dimmer Bypass
03-LPS	375 Watts 600 Watts 750 Watts 950 Watts 1150 Watts	Surface	Self-Diagnostics CEC-Title 20 Compliant Remote Test Switch Panel 4C- 4-output Circuit Switching 4AO-Adjustable Output/Dimmer Bypass Input Circuit Breaker Output Circuit Breaker



Emergency Driver for LED Lamps

Our dependable emergency driver provides regulated power to LED lamps during a power outage. Our emergency driver has versatile mounting options: inside, on-top or remote mount. Includes a push to test indicator standard.



Product Number	Output Voltage	Output Wattage
03-LEDEM-BP/DM-20W-E	180VDC	20 Watts



Push-to-Test Indicator Included

Constant-Power Emergency LED Drivers

Provides constant power output to the load during emergency mode operation. Suitable for installation inside, on-top, or in remote mount of the LED Strip Lights and other fixtures. Electronic limiting with normal operation resuming upon removal of fault. UL Listed, Field-installed.
 • CEC Title 20 Compliant standard on models -MV and -HV



Product Number	Current (mA)	Output Voltage (VDC)	Output Wattage (W)	Lumens (Lm)
03-LEDEM-CP-1200	390-156	20-50	7.8	1200
03-LEDEM-CP-2400	850-340	20-50	17.0	2400



Product Number	Current (mA)	Output Voltage (VDC)	Output Wattage (W)	Options
03-BLEM-CP-5	250-100	20-50	5	-C = Provided with 2' flex conduit on each end
03-BLEM-CP-10	535-214	20-50	10.7	
03-BLEM-CP-13	685-274	20-50	13.7	





MICRO-WAVE OR DAYLIGHT HARVESTING / OCCUPANCY SENSOR

13-HD406VRH-D

- Multi-volt: 120-277V
- Rated up to 3A @120V
- Operating Temperature of -35°C to 60°C
- Mounts up to 49ft
- Requires remote to adjust factory settings (HD03R)



CEILING MOUNTED PIR OCC SENSOR

13-OSC52V

- Replaces a standard light or fan switch.
- Time-delay adjustment from 10 seconds up to 30 minutes.
- Sensitivity adjustment.
- Light level sensing adjustment sets brightness value upon activation.



360° HIGH BAY OCC SENSOR

05-FL-OSFHU-RG-QC

- Passive Infrared Technology:
- Turn lights ON in response to the heat generated energy
- Mounts directly onto a luminaire
- Operational Mode: Auto ON, Auto OFF
- Time Delay: Adjustable (15 seconds up to 30 minutes)
- Coverage Range: High Bay mounting heights up to 25' mounting / 360° field
- 120/277VAC, 60Hz Voltage
- Load Requirements: 800VA at 120VAC



RF CONTROL

13-PPA401S

- Multi-volt: 120-277V
- 0-10V Dimming
- Operating Temperature of 0° - 40°C
- Rated up to 1200W
- Remote Required



BLUETOOTH CONTROL

13-PPA102S

- Multi-volt: 120-277V
- 0-10V Dimming
- Rated up to 13.1A
- Bluetooth Mesh
- App controlled



EXTERNAL SCREW-IN PIR SENSOR

07-HD07VR-PH-1

- 12VDC Input Power
- Screw in RCA Jack compatible with most standard receptacles
- Operating temperature of -20°C to 60°C
- Mounts up to 39ft
- Requires remote to adjust factory settings (HD05R)



3-PIN NEMA PHOTOCELL

08-JL-205C23-IP65

- Multi-volt: 120-277V
- Turns on at 6 lux, turns off at 50 lux
- Operating Temperature of -40°C to 70°C
- Rated up to 1800W
- Preset 5-30 second time delay



480V NEMA PHOTOCELL

08-26WA86

- Input Voltage of 480V
- Turns on at 10-20 lux, off at 30-60 lux
- Operating Temperature of -40°C to 70°C
- Rated up to 1800W



EXTERNAL SCREW-IN MICROWAVE SENSOR

07-HD07VR-MH-B-1

- 12VDC Input Power
- Screw in RCA Jack compatible with most standard receptacles
- Operating temperature of -20°C to 60°C
- Mounts up to 49ft
- Requires remote to adjust factory settings (HD05R)



PHOTOCELLS

**06-120/277V-BPC
06-120/277V-PPC2**

- Multi-volt: 120-277V
- Turns on at 10-20 lux, turns off at 30-80 lux
- Operating Temperatures of -40°C – 70°C
- Rated for up to 5A
- Preset 3-10 second time delay





180° PIR WALLBOX VACANCY & OCC SENSOR

13-OCC-VACSEN-WH-MV

- PIR detects motion from heat-emitting source
- Replaces a standard light or fan single-pole switch
- Automatic ON/OFF and manual ON / Automatic OFF operation
- Neutral wire required.
- LED Indicates motion was sensed
- Adjustable time delay from 15 seconds - 30 minutes
- Multi-volt



DIMMERS

**13-DWS-010V-T
13-DWS-010V-D**

- Multi-volt: 120-277V
- 0-10V Dimming
- Rated up to 600W
- Compatible with LED/CFL/Incandescent Lamps and Luminaires
- Single pole and 3 Way applications



Product Number	GFCI
13-GFCI-ST-20TR-WH-K	20 amp Self Testing Tamper
13-GFCI-ST-20TRWR-WH-K	20 amp Self Testing Tamper/WR
13-GFCI-ST-15TR-WH-K	15 amp Self Testing Tamper
13-GFCI-ST-15TRWR-WH-K	15 amp Self Testing Tamper/WR



Product Number	Receptacles
13-115R-S-WH	15 amp Duplex Single Recep.
13-120R-S-WH	20 amp Duplex Single Recep.
13-15R-D-WH	15 amp Decora Recep.
13-15R-D-TR-WH	15 amp Decora Recep. Tamper
13-15R-S-WH	15 amp Duplex Recep.
13-15R-S-TR-WH	15 amp Duplex Recep. Tamper
13-20R-D-WH	20 amp Indust Decora Recep.
13-20R-D-WH-TR	20 amp Indust Decora Recep. Tamper
13-20R-S-WH	20 amp COM Stand Duplex Recep.
13-DD30A-4S	Dryer/Range Receptacle, 30A
13-DD50A-4S	Dryer/Range Receptacle, 50A
13-TR20-DC	20 amp Tamper Decora Recep.
13-TR20-SC	20 amp Tamper Duplex Recep.
13-USB-15-TR	15 amp Receptacle USB Tamper
13-USB-20R-TR	20 amp Receptacle USB Tamper



Product Number	Switches
13-DS115	Single Pole Decora Switch 15 Amp
13-DS3115	3-way Decora Switch 15 Amp
13-DS415	4-way Decora Switch 15 Amp
13-TS115	Single Pole Toggle Switch 15 Amp
13-TS215	2-Way Toggle Switch Side 15 Amp
13-TS315	Duplex Horizontal Toggle Switch



Product Number	Face Plates
13-1T-WH	1 Gang Phone Jack
13-1J-WH	1 Gang Coaxial Jack
13-1RP-WH	1 Gang Single Recep. Plate
13-BP1-WH	1 Gang Blank Plate
13-BP2-WH	2 Gang Blank Plate
13-DDR-PL2-SS	Dryer Stainless Steel Plate
13-DP1-WH	1 Gang Decorative Plate
13-DP2-WH	2 Gang Decorative Plate
13-DP3-WH	3 Gang Decorative plate
13-DP4-WH	4 Gang Decorative Plate
13-DRP1-WH	1 Gang Duplex Recep. Plate
13-DRP2-WH	2 Gang Duplex Recep. Plate
13-TP1-WH	1 Gang Toggle Plate
13-TP2-WH	2 Gang Toggle Plate
13-TP3-WH	3 Gang Toggle Plate



ASK ABOUT OUR WHIPS, CORDS AND OTHER ACCESSORIES FOR YOUR PROJECT!



WIRE CONNECTORS

Broad offering of popular, standard types including Barrel, Winged and Winged Easy-turn and Push-in connectors:

Barrel		Winged/Winged Easy		Push-In	
Product Number	Color	Product Number	Color	Product Number	Ports/Color
15-P6001	Red	15-P1301	Red	15-PC25201	2-port Red
15-P2001	Baby Blue	15-N1001	Yellow (Easy)	15-PC25301	3-port Orange
15-P4001	Yellow	15-P1101	Yellow	15-PC25401	4-port Yellow
15-P3001	Orange	15-N2001	Red (Easy)		
		15-P1501	Big Grey		
		15-P1701	Big Blue		
		15-P9901	Green		
		15-P1201	Tan		



GOOF RINGS

- 50 Pack
- High Quality White Plastic Goof Ring for Can Lights & Down Lights
- Outside Diameter: Approximately 7 7/8" Inches or 20 Centimeters
- Inside Diameter: Approximately 5 7/8" Inches or 15 Centimeters.
- Replaces The Ring Of a 6 Inch Baffle Trim Can Light



CABLE TIES

- 100 pieces per bag
- Operating Temp: -4°F ~ 185°F
- 50 lb Tensile Strength

Product Number	Description	Color	Length (In.)	Width (in.)
16-850-SMN	Screw Mount Plenum Cable Tie	Natural	8	0.19
16-850-N100	UV Rated Plenum Cable Ties	Natural	8	0.19
16-1150-N100	UV Rated Plenum Cable Ties	Natural	11	0.19
16-1450-N100	UV Rated Plenum Cable Ties	Natural	14.5	0.19
16-850-B100	UV Rated Plenum Cable Ties	Black	8	0.19
16-1150-B100	UV Rated Plenum Cable Ties	Black	11	0.19
16-1450-B100	UV Rated Plenum Cable Ties	Black	14.5	0.19

Wholesale Lighting For LESS

We'd Love to Serve You

866-633-6883

costlesslighting.com



4200 Regent St. Suite 200
Columbus, OH 43219