COST LESS LIGHTING


06-CPHL

CANOPY LUMINAIRE
HIGH LUMEN

p. 866.633.6883 • f. 866.699.8099 • CostLessLighting.com

PROJECT	TYPE	CATALOG #





Model	Size (inches) & Weight (lbs)			
	L (in)	W (in)	H (in)	Weight
06-CPHL-272219L-5K	15	15	3.26	10.83

SERIES	NOMINAL LUMEN OUTPUT (SELECTABLE)	KELVIN
06-CPHL	272219L = 27,000 / 22,000 / 19,000 lm	5K 5000K

Specifications

Housing

- *Premium powder-coat, die cast aluminum, White housing.*

Electrical

- *Operating temperature (ambient): -40°C to 45°C (-40°F to 113°F) .*
- *Universal 120-277 AC voltage (50-60Hz) is standard.*
- *0-10V DC dimming drivers are standard.*
- *Input transient surge protection = 6kV.*
- *PF > 0.9; THD < 20%.*

Optical System

- *Polycarbonate lens.*
- *5000K (cool white) color temperatures.*
- *Provides a range of 19,000 to 27,000 nominal lumens.*
- *Long-life LEDs provide 173,000 hours of operation with at least 70% of initial lumen output (L70), and 52,000 hours with at least 90% of initial lumen output (L90).**
- *LED chromaticity based on < 6-step ANSI quadrangles.*
- *Color Rendering Index > 80.*

Mounting

- *Surface mounting.*

Code Compliance

- *cULus listed for wet locations.*
- *Complies with FCC Part 15, class A.*
- *IP65 rated for ingress protection.*

Warranty

- *5-year warranty on all electronics and housing.*

**L_{70} & L_{90} hours are IES TM-21-11 calculated hours.*

p. 866.633.6883 • f. 866.699.8099 • CostLessLighting.com

Accessories (order separately)

Mounting Option

ZZ-GOOFRING-12.5IN = 12.5" White Canopy Goof Ring / Back Plate
ZZ-GOOFRING-16IN = 16" White Canopy Goof Ring / Back Plate

Compatible Dimmers & Controls

Manufacturer	Model Number	Dimmer Range	Load Switching Capacity
Best Lighting	DWS-010V-T	10%-100%	600W
Best Lighting	DWS-010V-D	10%-100%	600W
Leviton	IP710-LFZ	10%-100%	1200W
Lutron	DVSTV	10%-100%	450W

Lumen Table & Electrical Data

Series	Measure-ments		Low Lumen	Mid Lumen	High Lumen
			5000K	5000K	5000K
06-CPHL-272219L-5K	Lumens		19,553	22,366	27,385
	Watts		120.2	139.4	177.3
	Efficacy		162.67	160.44	154.46
	Input Current (A)	120V	1.0	1.16	1.48
		240V	0.5	0.58	0.74
		277V	0.43	0.50	0.64

p. 866.633.6883 • f. 866.699.8099 • CostLessLighting.com

Photometric Data

06-CPHL-272219L-5K

Luminaire Data

Description	High Lumen Canopy 5K, Lumen Selectable
Total Lumens	27,385
Input Wattage	177
Efficacy (lm/W)	154
Spacing Criterion (0-180°)	1.28
Spacing Criterion (90-270°)	1.3

Photometric calculated at highest lumen setting.

Zonal Lumen Summary

Zone	Lumens	%Fixt
0-20°	3,425	12.5%
0-30°	7,319	26.7%
0-40°	12,071	44.1%
20-50°	13,579	49.6%
40-70°	12,464	45.5%
0-60°	21,364	78.0%
0-80°	26,280	96.0%
0-90°	26,964	98.5%
90-180°	421	1.5%
0-180°	27,385	100.0%

